

# COMMERCIAL SANDWICH PRODUCTS

Complete Line of Commercial Steel Sandwich Doors



### **Product Details**

Steel Commercial Sandwich Doors

### WARRANTY INFORMATION



Door: 10 yr



Hardware: 1 yr



Springs: 1 yr

## THERMAL RATING



0.29 (340S) 0.21 (350S / 354S)



9.0 (340S) 10.4 (350S / 354S)

- Steel Front and Back
- 1½" (340S) or 2" (350S / 354S)
- CFC Free Polystyrene Insulation
- 3 Window Designs
- 2 Standard + 3 Optional Colors

#### **Thermal Rating**







340S, 350S and 354S panels are all available with woodgrain embossment in flush design.



340S, 350S and 354S panels are all available with wood-grain embossment in microgroove design.



340S and 350S panels are available with woodgrain embossment in short raised panel deisgn in certain configurations.

## Window Design Options



- 1 24" X 6"
- 2 24" X 12"
- 3 Clear anodized full-view aluminum section

For all models, windows are available standard in black and optional white or color-matched brown.



Sandstone Microgroove Panel with 24" x 12" White Windows



White Flush Panel without Windows



White Short Raised Panel without Windows



White Microgroove Panel with 24" x 12" Black Windows

### **Product Options**

Steel Commercial Sandwich Doors - A Complete Line of Offerings to Meet Your Needs


= Standard = Optional = Unavailable


Model	340S Standard Duty	350S Heavy Duty	354S Industrial Duty
Section Thickness (in)	1-1/2	2	2 (24 Gauge Exterior)
Maximum Size Range (consult factory for doors over 18' h)	18'-2" w x 18' h	24'-2" w x 18' h	24'-2" w x 18' h
Design Options			
Flush	•	•	•
Microgroove	•	•	•
Short Raised Panel (in certain configurations)	0	0	
Texture	Woodgrain	Woodgrain	Woodgrain
Color Options			
White	•	•	•
Brown	•	•	•
Sandstone	•	•	
Black	•	•	
Silver Metallic (not available in short raised panel designs)	•	•	
Window and Frame Options (in)			
24 x 6 or 24 x 12 - Black Frames	•	•	•
24 x 6 or 24 x 12 - White, Brown, Sandstone, and Silver Metallic Frames	0	0	0
Clear Anodized Full-View Aluminum Section	0	0	0
Rope	•	•	•
Locks			
Slide Lock	•	•	•
T-Handle	0	0	0
Cylinder	0	0	0
Mini-Warehouse	0	0	0
Track Configuration			
Bracket Mount	•	•	•
Continuous or Reverse Angle (per weight and width rules)	0	0	0
Tapered Angle (2")	0	0	0
3" Track	0	0	0
Floor Seal			
Grey 3" Vinyl Floor Seal	•	•	•
Black 4" Vinyl Floor Seal (shipped separately)	0	0	0
Hardware			
14 ga. Hardware	•	•	•
11 ga. Hardware (end and center hinges)	0		0


#### **ADDITIONAL OPTIONS**

- 13 ball bearing sealed rollers 2" & 3"
- Higher Cycle Spring options: (25K, 50K & 100k)
- Optional Weather Seals: Vinyl Door Stop, Reverse angle jamb seal, header seal and bottom astragal standard & oversized

## Commercial Track Mounting Options







Typical Construction for Reverse Angle Door Width = Door Opening Width + 2 (i.e. 8'2", 10'2", 16'2", 20'2" etc.)



# SIX PRODUCTION PLANTS, ONE FAMILY

As one of the world's leading manufacturers of door systems, we're committed to providing the best quality, value, and selection. Whether residential, commercial or industrial, we have the solutions you're looking for. Each Hörmann product gives you the perfect array of benefits and options to satisfy your customers.











#### USA

Toll Free: 800.365.3667 Email: info@hormann.us Website: hormann.us

#### Canada

Toll Free: 866.792.9968 Email: info@hormann.ca Website: hormann.ca

#### Mexico

Toll Free: 52 (81) 8308 7481 Email: info@hormann.com.mx

Website: hormann.mx




























Follow us on social media







