


Product Data Sheet

HD-DD 3065

HD SERIES Direct Drive Rubber Door

HÖRMANN

Features



The HD-DD 3065 offers the full heavy duty rubber door design for harsh, demanding environments while providing the speed and durability industry demands.

- The HD-DD 3065 offers the full heavy duty rubber door design for harsh, demanding environments.
- A variable frequency drive (VFD) provides soft start and soft stop, ensuring smooth operation and extend life of the mechanical system
- Springless direct drive system is simple to install, low maintenance while providing high-speed operation.

Technical Data		Remark	
Application		Interior / exterior	
Speed	Opening	Closing	"up to" maximum speed for this model depending on door size
	64 in/s (1.6 m/s)	30 in/s (0.8 m/s)	
Control Box (W x H x D)		11.625" x 15.75" x 8.5" (295 mm x 400 mm x 215 mm)	
Roll-up Technology		Roll tube with precision-welded axles	
Door Construction	Size Range	6'-0" (1830 mm) up to 30'-0" (9144 mm) wide 6'-0" (1830 mm) up to 30'-0" (9144 mm) high	
	Mounting angle / guide track assembly profile (W x D)	5.25" x 9" (140 mm x 230 mm) 9.25" x 9" (230 mm x 230 mm)	
	Roll Tube Diameter	8.625" (219 mm) x 0.322" (8.2 mm) thick wall	
	Window Size	16" x 16" (406 mm x 406 mm), 1/8" (3 mm) thick	
Required Headroom		32.5" (825 mm) 37" (940 mm)	
Drive Mechanism		Direct drive operator with manual chain hoist	
Counterbalance System		Not required	
Braking		Control box activated 24 VDC disc brake	
Cycleability / Maintenance		Up to 500 per day (size dependent) / Inspection every three months	
Safety Features		Integrated in-line light grid, manual chain hoist	
Resistance to Wind Load		20 pounds per square foot (1.0 kPa) windclass 5	
Fire resistance rating		Non-rated, Non-conforming exit	
Warranty		Curtain - Limited lifetime Operator - 5 years or 1 million cycles / General - 2 years	

Product Data Sheet (Continued)

HD-DD 3065

HD SERIES Direct Drive Rubber Door



Materials and Finishes		
Curtain	Standard 1/4" (6 mm) / Black SBR (Styrene-Butadiene Rubber)	Optional: 1/4" (6 mm) Blue or Grey EPDM (Ethylene Propylene Diene Monomer), Black Nitrile, Black MSHA (Mine Safety and Health Administration)
Curtain Temperature Rating	SBR: -40°F (-40°C) to 185°F (85°C)	Grey EPDM: -63°F (-53°C) to 185°F (85°C) Blue EPDM: -56°F (-49°C) to 185°F (85°C)
Guides	5" (127 mm) aluminum extrusion	
Mounting Angles	Rollformed high strength galvanized steel, 10 gauge with gussets	
Guide Guards	Rollformed high strength galvanized steel, 10 gauge	
Bottom Bar	Extruded aluminum weighted bottom bar with patented pivoting arms	
Endplates	Zinc dichormate plated steel	
Truss	Fabricated steel construction, painted	
Roll Tube	Galvanized steel	
Idler Barrel	Galvanized steel 6.25 in (159 mm) diameter x (4 mm) thick wall	
Weather Seals	Self sealing rubber curtain/guides, EPDM loop seal on bottom bar, brush seal at lintel	
Electric Door Operator	DD direct drive operator	Optional stainless steel motor
Control Box	Smart Start™ NXT with VFD, powder coated enclosure	Optional Smart Start XL with heater / Optional stainless steel enclosure
Hood and Motor Cover (Optional)	18 gauge galvanized steel	
Energy Analysis		
Visible Transmittance (Tvis)	N/A	
Solar Heat Gain Coefficient (SHGC)	N/A	
Thermal Resistance (R-value)	0.73 hr·ft²·°F/BTU (0.13 m²·K/W)	ASTM C518 – 10
Heat Transfer Coefficient (U-value)	1.36 BTU/hr·ft²·°F (7.74 W/m²·K)	ASTM C518 – 10
Acoustic Insulation	Sound transmission Class (STC) 28 dB Outdoor-Indoor transmission class (OITC) 23 dB	ASTM E 90-09 / E 413-10 / E1332 - 10a
LEED Credit (Potential)	N/A	
Electrical		
Electric Door Operator (Motor)	GFA Elektromaten 2.0 to 5 hp (1.5 to 3.75 kW) varies by door size	NEMA Type 3 / IP54
Operating Voltage	230-272 VAC, 3 PH, 60 Hz	Voltage dependant on door/operator size
Control Box	6.7 hp (5 kW) variable frequency drive rated for operator voltage	NEMA Type 4X / IP66, UL/CUL/CE Listed
Standard Power Requirement	208-600 VAC, 3 PH, 60 Hz	Buck-Boost transformers may be required at 208v, 50Hz available
Full Load Amps	7.6 to 12.4 A	Operator
Disconnect	Fuse: 20 A, Class K	Service to control box supplied by others



TNR Industrial Doors | 200 Fairview Road, Unit 2 | Barrie, ON L4N 8X8
1-866-792-9968 | 705-792-9968 | tnrdoors.com