


| | |
|-----------------------|------------------------------|
| MODEL: | SR9000 LHR |
| CUSTOMER: | - |
| ADDRESS: | - |
| CITY & STATE: | - |
| JOB: | - |
| LOCATION: | - |
| COMPANY: | - |
| SIZE: | DW=- DH=- |
| MOTOR LOCATION: | RIGHT LEFT |
| CONTROL BOX LOCATION: | RIGHT LEFT |
| CONTROL BOX TYPE: | 3PHASE |
| VOLTAGE: | 208V 230-240V 360-480V F575V |
| WIRING: | NXT |
| VISION AREA: | |
| WINDOWS: | QTY. OF SLATS STARTING AT |
| VENTED: | QTY. OF SLATS STARTING AT |
| OPTIONS: | |
| INDUCTION LOOP SYSTEM | - |
| RADAR MOTION SENSOR | - |
| NOTES: | |

- 1.) STEP UP TRANSFORMER SUPPLIED FOR VOLTAGES UNDER 480VAC.
- 2.) STEP DOWN TRANSFORMER SUPPLIED FOR VOLTAGES OVER 480VAC.



TRACK DETAIL

ALL DIMENSIONS ARE IN INCHES.
 * NECESSARY SPACE REQUIREMENT FOR MAINTENANCE.
 **SPACE REQUIRED TO FIT AND DISMANTLE THE OPERATOR.
 CONTROL BOX PROJECTION IS 11 INCHES.
 DRAWING SHOWN RIGHT HAND, LEFT HAND OPPOSITE.

| | | | | |
|---|-------------|------|------|----|
| GENERAL TOLERANCES ACC. TO DIN ISO 2768-MK PLASTIC MOLDED PARTS ACC. TO DIN 16901-130 GEOMETRICAL TOLERANCES ACC. TO DIN ISO 1101 | | | | |
| REV. | DESCRIPTION | DATE | ECON | BY |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |
| - | - | - | - | - |

HORMANN
 117 STARPOINTE BOULEVARD
 BURGETTSTOWN, PA 15021-9506
 PH: +1 (800) 365-3667 FAX: 724.385.9151
 www.hormann.us

| | |
|-------------|-----------------------|
| TITLE: | STEEL RANGER 9000 LHR |
| MODEL: | - |
| DRAWING #: | - |
| PAPER SIZE: | ANSI "B" |
| PAGE: | 1 OF 1 |
| SCALE: | 1:1 |
| QTY: | - |
| ENGINEER: | - |
| DRAWN: | 05/26/2022 |

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE