


## COMMERCIAL POLYURETHANE PRODUCTS

Industry-Leading Energy Efficiency and Engineering



### **Product Details**

Steel Commercial Polyurethane Insulated Doors





Galaxy Painted Micgrogroove with 2 Full View Aluminum Sections



Metallic Silver Micgrogroove with Full View Aluminum Section



Galaxy Painted Micgrogroove Without Windows

with stucco embossment.


440U and 450U panels are

produced in microgroove design



440U and 450U panels are also produced in flush design with woodgrain embossment.

## Window Design Options



24" X 6"
 24" X 12"

3 Clear anodized full-view aluminum section

For the 440U and 450U, window frames (options 1 and 2) are available **standard in black** and **optional** in white, brown, sandstone, grey (to pair with silver metallic), and in custom color (Galaxy Paint Sytstem).

Full-view sections (option 3) may also be painted to match the door.



Galaxy Painted Microgroove with Full View Aluminum Section

### **Product Options**

#### Commercial Polyurethane Insulated Doors - Unmatched Efficiency and Durability

<ul> <li>= Standard</li> </ul>
$\bigcirc$ = Optional
— = Unavailable

Model	440U 1-1/2" Sections	450U 2" Sections
Maximum Size Range	20'-2" w x 18' h	26'-2" w x 18' h
R-Value	15.7	18.4
Design Options	Microgroove Flush	Microgroove Flush
Texture	Stucco: Microgroove Wood Grain: Flush	Stucco: Microgroove Wood Grain: Flush
Color Options		
White	•	•
Brown	•	•
Sandstone	•	•
Metallic Silver	•	•
Galaxy Paint	•	•
Glass Options (in)		
24 x 6 or 24 x 12 Black Frames	•	•
24 x 6 or 24 x 12 White, Brown, Sandstone, Grey (to pair with Metallic Silver), or Custom Color (Galaxy Paint System) Frames	0	0
Clear Anodized or Color-Matched Full-View Aluminum Sections	0	0
Rope	•	•
Locks		
Slide Lock	•	•
T-Handle	0	0
Cylinder	0	0
Mini-Warehouse	0	0
Track Configuration		
Bracket Mount	•	•
Continuous or Reverse Angle (per weight and width rules)		0
Tapered Angle (2")	0	0
3" Track	0	0
Floor Seal		
Grey 3" Vinyl Floor Seal	•	•
Black 4" Vinyl Floor Seal (shipped separately)	0	0
Hardware		
14 ga. Hardware	•	•
11 ga. Hardware (end and center hinges) - Consult Factory	0	0

#### ADDITIONAL OPTIONS

• Epoxy painted track and hardware

• 13 ball bearing sealed rollers 2" & 3"


• Higher Cycle Spring options: (25K, 50K & 100k)

• Optional Weather Seals: Vinyl Door Stop, Reverse angle jamb seal, header seal and bottom astragal standard & oversized


## Commercial Track Mounting Options

#### Bracket Mounted Track






Continuous Angle Track







Typical Construction for Reverse Angle Door Width = Door Opening Width + 2 (i.e. 8'2", 10'2", 16'2", 20'2" etc.)

# HÖRMANN NORTH AMERICA

Sparta, TN - North American Headquarters / Sectional Doors

# SIX PRODUCTION PLANTS, ONE FAMILY

As one of the world's leading manufacturers of door systems, we're committed to providing the best quality, value, and selection. Whether residential, commercial or industrial, we have the solutions you're looking for. Each Hörmann product gives you the perfect array of benefits and options to satisfy your customers.



USA Toll Free: 800.365.3667 Email: info@hormann.us Website: hormann.us

Canada Toll Free: 866.792.9968 Email: info@hormann.ca Website: hormann.ca

Mexico Toll Free: 52 (81) 8308 7481 Email: info@hormann.com.mx Website: hormann.mx





AVAILABLE FROM:

















