



5&2
WARRANTY
YEAR

SPEED-MASTER® 2600 L

High Performance Door

HÖRMANN

Speed-Master® 2600 L

Industrial high cycle applications up to 24'0" w x 24'0" h

Features

Application	Interior or exterior
Model / Classification	2600 L / Fabric
Size range	Maximum 24'0" w x 24'0" h / Maximum 400 sq. ft.
Technology	Direct-drive, sectional panel
Operating speed	Opening 36" IPS Closing 30" IPS
Panel	Patented, sectional design, heavy-duty aluminum hinge profiles Panel: reinforced, puncture resistant 1/8" thick 90 oz. / sq. yd. Bulldog XT material Colors: orange, blue, black, gray
Thermal insulation U-value (metric) in W/(m ² ·K) U-value (imperial) in BTU/(h·ft ² ·°F)	2.66 0.47
Vision	Two full-width, clear PVC starting approximately 36" off floor
Custom panel imprints	Logos, photos or text digitally printed onto panel. UV treated and waterproof. Maximum image size 7'0" wide X 3'0" high
Resistance to wind load	Consult factory
Guide tracks	10" w x 7" projection galvanized steel. Optional: Windlocks for applications with excessive windload
Hoods	Optional: Galvanized steel
Safety	8'0" high light curtain built into guide tracks
Control	NEMA 4X Smart Start™ NXT UL, 3-ph, 480 v (208-230, 575 v w/ transformer.)
Activation options	Push button / Pull cord / Motion detector / Presence detector Induction loop detector (wire/sealant by others) / Remote control Touchless switch (several models) Consult factory for additional options
Accessories	LED Lite-Advance / ScanProtect / Wireless Crash Alert / Remote Keypad / Energy Analysis Report
Emergency	Chain hoist Optional: Hand crank
Compliance	Door complies with requirements of UL325
Warranty	5 & 2 Year: Motor/gearbox (excluding catch) and panel material 5 years, materials & workmanship. All other mechanical and electrical components free from defects, 2 years



Ideal for demanding industrial applications

Demanding industries such as manufacturing, distribution, transit, steel plants, airports, etc., will benefit from the simple design of the 2600 L. For exterior mounting doors, options like a roll and motor cover along with motor / gearbox heater make it possible to accommodate high traffic exterior door applications during cold weather.



Smart Start™ NXT NEMA 4X UL control box simplifies installation

A distribution block accepts the activation and protection device wiring; main power cables feed through pre-drilled holes on the bottom of the box where the individual wires, with pre-wired removable terminal blocks, plug into the circuit board. Extra ports on the control board allowing for firmware upgrades and future expansion. A USB port is available for maintenance monitoring.

USA

Toll Free: 800.365.3667
Email: info2@hormann.us
Website: hormann.us

Canada

Toll Free: 866.792.9968
Email: info@hormann.ca
Website: hormann.ca

