

Product Data Sheet

HD-HD 2565
HD SERIES Hybrid Door



Lighter curtain options for less demanding environments while still maintaining the speed and durability of the direct drive system.

- The HD-HD 2565 offers a hybrid alternative of a lighter rubber curtain or 88 oz fabric curtain.
- Springless direct drive system is simple to install, low maintenance while providing high-speed operation.
- A variable frequency drive (VFD) provides soft start and soft stop, ensuring smooth operation and extend life of the mechanical system

Technical Data	Imperial	Metric	Remark
Application	Interior / Exterior		
Speed	Opening: 63 in/s Closing: 29 in/s	Opening: 1.60 m/s Closing: 0.70 m/s	
Control Panel	W x H x D (in) 11.625 x 15.75 x 8.5	W x H x D (mm) 295 x 400 x 215	
Roll-up Technology	Roll tube with precision-welded axles		
Size Range	Width 6 ft 0 in up to 25 ft 0 in Height 6 ft 0 in up to 22 ft 0 in	Width 1.83 m up to 7.62 m Height 1.83 m up to 6.71 m	
Mounting angle / Guide track Assembly Profile	W x D (in) 5.25 x 9 9.25 x 9	W x D (mm) 140 x 230 230 x 230	Steel mount Concrete mount
Roll Tube Diameter	8.625 in x 0.177 in thick wall	219 mm x 4.5 mm thick wall	
Visible Material Height (Window Size)	16 in x 16 in, ½ in thick	406 mm x 406 mm 3 mm thick	
Required Headroom	25.5 in	650 mm	
Drive Mechanism	Direct drive operator with manual chain hoist		
Counterbalance System	Not Required		
Braking	Control box activated 24 VDC disc brake		
Cycleability / Maintenance	Up to 500 per day / Inspection every three months		
Safety Features	Integrated in-line light grid, manual chain hoist		
Resistance to Wind Load (Max per Door Width)	20 psf, wind class 5	1.0 kPa wind class 5	ANSI / DASMA 108-2002
Fire Resistance Rating (Behavior)	Non-rated, Non-conforming exit		
Manufacturer Warranty	Curtain - Limited lifetime Operator - 5 years or 1 million cycles / General - 2 years		

Product Data Sheet

HD-HD 2565
HD SERIES Hybrid Door



Materials & Finishes	Imperial	Metric	Remark
Guides	5 in aluminum extrusion guards	127 mm aluminum extrusion guards	
Mounting Angles	Rollformed high strength galvanized steel, 10 gauge with gussets		
Guide Guards	Rollformed high strength galvanized steel, 10 gauge		
Roll Tube	Galvanized steel		
End Plates	Zinc dichormate plated steel		
Weather Seals	Self sealing rubber curtain / guides, EPDM loop seal on bottom bar, brush seal at lintel		
Curtain	Standard ½ in Black SBR (Styrene-Butadiene Rubber)	Standard 4 mm Black SBR (Styrene-Butadiene Rubber)	Optional 88 oz (2.5 mm) Blue, Grey, Orange PVC (Poly Vinyl Chloride)
Curtain Temperature Rating	SBR: -40°F to 185°F	SBR: -40°C to 85°C	PVC: -22°F (-30°C) to 176°F (80°C)
Bottom Profile (Bar) Door Slat	Extruded aluminum weighted bottom bar with patented pivoting arms		
Electric Door Operator	Cast aluminum direct drive operator		
Control Panel	Smart Start™ NXT with VFD, powder coated enclosure		Optional Smart Start XL with heater / Optional stainless steel enclosure
Hood and Motor Cover (Optional)	18 gauge galvanized steel		
Truss	N/A as standard		Included with guide mount windbar only - Fabricated steel construction, painted
Idler Barrel	Galvanized steel 6.25 in diameter x 0.16 in thick wall	Galvanized steel 159 mm diameter x 4 mm thick wall	
Energy Analysis	Imperial	Metric	Remark
Thermal Resistance (R-value)	N/A		ASTM C518 – 10
Heat Transfer Coefficient (U-value)	N/A		ASTM C518 – 10
Acoustic Insulation	Sound transmission Class (STC) 28 dB Outdoor-Indoor transmission class (OITC) 23 dB		ASTM E 90-09 / E 413-10 / E1332 - 10a
Electrical	Description		Remark
Electric Door Operator	GFA Elektromaten 2.0 to 5 hp (1.5 to 3.75 kW) varies by door size		NEMA Type 3 / IP54
Operating Voltage (Motor)	230 - 272 VAC, 3 PH, 60 Hz		Voltage dependent on door / operator size
Control Panel	6.7 hp (5 kW) variable frequency drive rated for operator voltage		NEMA Type 4X / IP66, UL/CUL/CE Listed
Standard Power Requirement (to Control Box)	208 - 600 VAC, 3 PH, 60 Hz		Buck-Boost transformers may be required at 208v, 50Hz available
Full Load Amps	7.6 to 12.4 A		Operator
Disconnect	Fuse: 20 A, Class K		Service to control box supplied by others



TNR Industrial Doors | 200 Fairview Road, Unit #2 Barrie, ON Canada L4N 8X8
1-866-792-9968 | 705-792-9968 | hormann.ca